



Numbering Head

H type

(Hand changing type)



- Turn the knob, and change characters manually
- For marking that is not necessary to change characters frequently e.g.) Lot-number, the date of manufacture, etc.
- Any random characters can be set
- Standard specification
 - Character size : 1.0, 1.5, 2.0, 2.5, 3.0, 4.0, 5.0, 6.0 mm
 - Typeface : YAMADA font 0-9, A-Z (capital letter), [—], [/], [.], [~]
 - Shank size : 1H / 1S(H) = 16 mm diameter, 2H / 3H = 25 mm diameter
 - Character ring : 10 letters for a digit (12 letters are optional)
- Options
 - a-z (small letter), all characters of customer designated special font, logo, another symbols, custom shank size, special head holder, etc.

Required press machines. Stamping is not possible only this tool.

A type

(Automatic changing type)




- Built-in an automatic feed function for digits
- Suitable for marking serial numbers
- Manufacturing numbering head of 2-marking in a unitary scale is available
- Standard specification
 - Character size : 1.0, 1.5, 2.0, 2.5, 3.0, 4.0, 5.0, 6.0 mm
 - Typeface : YAMADA font 0-9, A-Z (capital letter), [—], [/], [.], [~]
 - Shank size : 1A / 1S(A) = 16 mm diameter, 2A / 3A = 25 mm diameter
 - Character ring : 10 letters for a digit (12 letters are optional)
- Options
 - a-z (small letter), all characters of customer designated special font, logo, another symbols, custom shank size, special head holder, etc.

Required press machines. Stamping is not possible only this tool.

N type

(Hand and Automatic changing type)



- Combination of Hand [H] and Automatic [A] changing types
- Suitable for marking lot-numbers and serial numbers
- Standard specification
 - Character size : 1.0, 1.5, 2.0, 2.5, 3.0, 4.0, 5.0, 6.0 mm
 - Typeface : YAMADA font 0-9, A-Z (capital letter), [—], [/], [.], [~]
 - Shank size : 1N / 1S(N) = 16 mm diameter, 2N / 3N = 25 mm diameter
 - Character ring : 10 letters for a digit (12 letters are optional)
- Options
 - a-z (small letter), all characters of customer designated special font, logo, another symbols, custom shank size, special head holder, etc.

Required press machines. Stamping is not possible only this tool.

PI type

(Parallel Insertion type)



- Character stamps are inserted individually
- Suitable for marking lot-number, model, the date of manufacture, etc.
- Any random characters can be set
- Standard specification
 - Character size : 1.0, 1.5, 2.0, 2.5, 3.0, 4.0, 5.0, 6.0 mm
 - Typeface : YAMADA font 0-9, A-Z (capital letter), [—], [/], [.], [~]
 - Shank size : 1 / 1S = 16 mm diameter, 2 / 3 = 25 mm diameter
- Options
 - a-z (small letter), all characters of customer designated special font, logo, another symbols, custom shank size, special head holder, etc.

Required press machines. Stamping is not possible only this tool.

HS type

(Hot Stamping type)



- Basic specification is A or PI types
- Built-in heater and thermostat
- Suitable for marking on resin molded item, etc.
- Standard specification
 - Character size : 1.0, 1.5, 2.0, 2.5, 3.0, 4.0, 5.0, 6.0 mm
 - Typeface : YAMADA font 0-9, A-Z (capital letter), [—], [/], [.], [~]
 - Shank size : 1HS / 1S(HS) = 16 mm diameter, 2HS / 3HS = 25 mm diameter
 - Character ring : 10 letters for a digit (12 letters are optional)
- Options
 - a-z (small letter), all characters of customer designated special font, logo, another symbols, custom shank size, special head holder, etc.

Required press machines. Stamping is not possible only this tool.

K type

(Hand-knocking type)



- Not required press machines
- Hit by a hammer and mark multiple digits at once
- Standard specification
 - Character size : 2.0, 2.5, 3.0, 4.0 mm
 - Typeface : YAMADA font 0-9, A-Z (capital letter), [—], [/], [.], [~]
 - Character ring : 10 letters for a digit (12 letters are optional)
- Options
 - a-z (small letter), all characters of customer designated special font, logo, another symbols, etc.

YAMADA Standard Typeface (H:W=2:1)

0 1 2 3 4 5 6 7 8 9 A B C D E F G H I J K L M N P Q R S T U V W X Y Z



YAMADA MACHINE TOOL CO.,LTD.

Marking System Division

1-10-13, Uemine, Saitama-shi, Saitama, Japan 3380014

TEL +81-48-851-1122 FAX +81-48-851-1125

URL : <http://www.yamada-mt.co.jp>

E-Mail : marking@yamada-mt.co.jp

※ Please contact us by e-mail for inquiries.